

JIH-250R ROTARY HYDRAULIC PRESS

JIH-250R ROTARY HYDRAULIC PRESS

MODEL	JIH-250R
Motor	5 HP
Punching force	8 ton
Table height	725 mm
Table area	50 x 240 mm
Stroke	150 mm
Punching height	260 mm
Mold Number	4 pieces
Net / Gross weight	450 kgs
Machine dim. (L x W x H)	1,050 x 1,050 x 1,800 mm
Packing dim. (L x W x H)	1,170 x 1,170 x 2,000 mm



JIH-250 HYDRAULIC PRESS

JIH-250 HYDRAULIC PRESS

MODEL	JIH-250 A	JIH-250 B	JIH-250 C	JIH-250 D
Punching force	8 ton	10 ton	15 ton	20 ton
Motor	3 HP	3 HP (5HP opt. for increasing production)	5 HP (7.5HP opt. for increasing production)	7.5 HP (7.5HP opt. for increasing production)
Stroke	150 mm	150 mm	150 mm	150 mm
Punching height	240 mm	260 mm	260 mm	349 mm
Hydraulic pressure	150 kgs / cm ²	170 kgs / cm ²	180 kgs / cm ²	180 kgs / cm ²
Table area	240 x 500 mm	240 x 520 mm	340 x 550 mm	325 x 557 mm
Table height from floor	740 mm	840 mm	930 mm	979 mm
Machine dim. (L x W x H)	600 x 550 x 1,680 mm	700 x 550 x 1,825 mm	800 x 650 x 2,150 mm	1,253 x 973 x 2,153 mm
Packing dim. (L x W x H)	720 x 670 x 1,860 mm	820 x 670 x 2,005 mm	920 x 770 x 2,330 mm	1373 x 1093 x 2333 mm
Net / Gross weight	290 / 380 kgs	350 / 440 kgs	550 / 650 kgs	990 kgs / 1100 kgs



JIH-170 COPY MILLING MACHINE

1. Designed for irregular milling on irregular aluminum door and window frame.
2. The right level control cross and longitudinal movement of milling head.
3. The left level control vertical movement of milling head.
4. Extremely smooth motion allows for effortless milling operations.
5. Workpiece clamping is pneumatically operated.
6. Coolant is conveniently controlled by simply pressing a switch on the left level.
7. Template for copy milling.
8. Oil mist system for cooling the cutter.

JIH-170 COPY MILLING MACHINE

MODEL	JIH-170 A	JIH-170 B
X travel	280 mm	340 mm
Y travel	120 mm	240 mm
Z travel	150 mm	180 mm
Table area	630 x 180 mm	680 x 300 mm
Air pressure	6 kgs / cm ²	6 kgs / cm ²
Motor	1 HP (2P)	2 HP (2P)
Spindle speed	12,000 R.P.M.	12,000 R.P.M.
Table height from floor	815 mm	808 mm
Chuck size	6, 8, 10 mm (opt.)	6, 8, 10 mm (opt.)
Machine dim. (L x W x H)	780 x 630 x 1,660 mm	990 x 900 x 1,660 mm
Packing dim. (L x W x H)	900 x 750 x 1,860 mm	1110 x 1020 x 1,860 mm
Net / Gross weight	156 / 220 kgs	205 / 280 kgs

