BENDING MACHINE BM76 MACKMA

Perfect bends and innovation, like a straight line.

Right and left hand bending Underhead bending Integrated connection for pipe deburring tool Variable speed








Pipes Bending machine BM76 Guideless, electric, semi-automatic and manual.

















BENDING MACHINE BM76 MACKMA

Tube and Pipe Bending machine BM76, non mandrel, electric, semi-automatic.

The **BM76 Bending Machine** is **THE ONLY non mandrel pipe bending machine** able to bend tubes and pipes to the left or right, by means of a reversible die holder, designed and patented by us. Other unique benefits include a connection for the installation of a useful internal/external tube deburring tool.

The innovative design allows the bending of pipes up to 76 mm in diameter and 3 mm in wall thickness. With a maximum of 380 mm centre line radius it is capable of maximum performance for this size of machine, even in the most demanding markets.

The bend rotation speed [1 to 2 RPM] is monitored by a dedicated inverter, to ensure the correct bending speed according to the diameter and thickness of the tube.

The compact "cantilever head" allows bending complex component shapes that may require the tube passing under the gearbox assembly.

The modular design of the bending shaft assembly also allows the use of most competitors tooling, reducing long term tooling costs. The inverter-controlled motor reduces energy consumption to a minimum.

The machine is mounted on precision casters for effortless movement around busy workshops and sites **Mackma** uses only 100% high quality Italian components to ensure long-term reliability.

Testament to the high quality of their machines is Mackma's standard 2 year warranty.



The image shown above is understood as a preliminary indication. MACKMA reserves the right to change form and function which are used exclusively for innovative improvements.



Via Volla snc 03030 Piedimonte San Germano (FR) Tel. +39 0776 404326 - 403489 Fax +39 0776 403460

Fax +39 0776 403460 info@mackma.com www.mackma.com



Industrial Tools, Tubular furniture
Automotive/Motorcycle
Dairy and Marine
Sport and fitness, Hydraulics
Factory maintenance... and many others...

MAIN TECHNICAL DATA BM76

Pipe Max Outer Diameter 76 mm Max Torque 10.000 N/mDiameter using FE - 42 kg/mg 76x3 mm Diameter using FE - 35 kg/mg 70x5 mm Diameter using AISI 304/316 - 65 kg/mg 70x4 mm Maximum radius 380 mm Height of the head 315 mm Projection of the head 384 mm 180° Max curvature angle Minimum rotation speed 1 rpm Maximum rotation speed rpm Bending direction rightward and leftward Electric tension V 440 Max installed power 1,8 KW Weight 306 Kg Dimensions (WxhxL) 700x1120x972 mm Operating temperature $0 - 50^{\circ}$



Ed.1/2015 EN

RATION