



SELECTA A DOUBLE HEAD CUTTING OFF MC

Gemma Group srl - Via Dante Alighieri 6, 47852 Coriano (RN) - Italy 0039 0541 905810 www.gemma-group.com info@gemma-group.com

SELECTA A





- Double head cutting off machine with a fixed sawing head on the left and one movable on the right side. Automatic positioning of the movable head.
- Rotation and tilting of both blades for compound cuts
- Electronic pivoting of the head inwards/outwards range 22,5° - 90° - 140°.
 Electronic tilting of the head range 90° - 45°.
- Lubrication by micro-drop oil

- Brushless motor for axe positioning managed by servodrive.
- Numerical control with 3 positioning axes of the latest generation integrated in the function of a personal computer with 10,4" colour display TOUCH SCREEN.
- Software HICAM 2 for creating and controlling, highly ergonomic and of easiest use.
- Possibility of tele-assistance via internet. Pc with Windows 10 + wifi.

STANDARD EQUIPMENT

Nr. 2 TCT Saw Blades 600mm Safe guards on the cutting area Nr.4 Vertical pneumatic clamps Micro drop oil lubrication Air gun 6mtrs length Movable side support Pneumatic central support Air filter

OPTIONALS

Extension length one meter (6 mt) TCT Saw Blade D.600mm (spare) Nr.2 Horizontal pneumatic clamps Label printer Motorized belt conveyor (5 mt) Motorized belt conveyor (6 mt) Safety protection with photocells

SELECTA A

GENERAL SPECIFICATIONS

| Blade diameter: | 600 mm |
|---|---|
| Spindle diameter: | 30 mm |
| Number of blade revs: | 2760 giri/1' r.p.m. |
| Cutting speed: | 72 m/sec |
| Advancement speed : | adjustable |
| Minimum cutting length (between two blades) : | 450 mm |
| Maximum cutting length (between two blades) : | 5000/6000 mm |
| Air consumption for cycle : | 32 NI. |
| Cutting angles : | 22,5° ÷ 145° Rotation / 90 ÷ 45 Inclination |
| Working pressure: | 7 bar |
| Motor power: | 50 Hz / 3 kW |
| Motor power: | 60 Hz / 4 kW |

| | PROFILO: capacità taglio (mm) PROFILE: cutting capacity (mm) | | |
|-----|---|-------------------|--|
| | | | |
| 90° | 200x200 | 400x150 / 450x90 | |
| 45° | 170x170 | 310x100 / 275x150 | |

| | - | kg | - |
|-----|----|------|----------------|
| mm | kW | kg | mm |
| 600 | 3 | 3400 | 7950x1850x2150 |

