## **» MEGA HORNET 2000**





# SCALABILITY FOR YOUR PROFITABILITY

; you boost your , speed, and

scalability. Perfect for the most demanding cutting environments, MEGA HORNET 2000 provides decades of reliable service to shipyards, service centers, contract shops, manufacturers and more.

#### FEATURING



#### **REMARKABLY VERSATILE**

Machine easily adapts to different work environments.

- · 2 tool carriers for increased efficiency
- Flexible dimensional width and length configurations
- Zoned air downdraft or water table compatible



#### **CONTOUR BEVEL SYSTEM**

Increases output by eliminating timeconsuming secondary finishing processes.

- · Weld-ready beveled parts
- Produces bevels 360° around parts at up to +/- 52°



#### **POWERFUL DRIVE SYSTEM**

Tackle the toughest industrial project with power and precision.


- Long-lasting, dependable operation
- Industry's most reliable AC servo amplifiers
- $\cdot~$  EtherCAT communication protocol




## **MACHINE SPECIFICATIONS**

Positioning Accuracy Repeatability   +/005" (.127 mm)* +/001" (.025 mm)* * Measured in a 60" x 60" area (1.5 m x 1.5 m)							
	8 ft (2.5 m)	10 ft (3.0 m)	12 ft (3.7 m)	14 ft (4.3 m)	16 ft (4.9 m)	18 ft (5.5 m)	20 ft (6.1 m)
Effective Cutting Width (A)	96" (2.5 m)	120" (3.0 m)	144" (3.7 m)	168" (4.3 m)	192" (4.9 m)	216" (5.5 m)	240" (6.1 m)
Effective Cutting Length (B)	120" (3.0 m) minimum						
Overall Machine Length (C)	Nominal Cutting Length +72" (1.83 m)						
Overall Machine Height (D)	101" (2.6 m)						
Overall Machine Width (E)	187" (4.7 m)	211" (5.4 m)	235" (5.9 m)	259" (6.6 m)	283" (7.2 m)	307" (7.8 m)	331" (8.4 m)
Width Between Rails (F)	115" (2.9 m)	139" (3.5 m)	163" (4.1 m)	187" (4.7 m)	211" (5.4 m)	235" (6.0 m)	259" (6.6 m)
Distance from Floor to Gantry (G)	41" (1.05 m)						
Gantry Parking Space	96" (2.4 m)						
Suggested Cutting Table Slat Height	26"-32" (0.66 m-0.81 m)						
The number tool carriages on the gantry beam affects actual effective cutting width. Verify your application with factory before ordering.							
Maximum Traverse Speed	1,000 IPM (30 mpm)						
Maximum Number of Tool Carriages	12 Total–1 Master & 11 Slave Carriages						
Maximum Number of Plasma Stations	4						
Maximum Plasma Production Capacity	2" (50 m)						
Recommended Plasma Systems	MAXPRO200™, HPR400XD™, HPR800XD™, XPR300™						
Maximum Number of Oxy-Fuel Stations	12						
Maximum Oxy-Fuel Production Capacity	12" (300 m)						
Input Power — Cutting Machine	480 VAC   3-Phase   50-60 Hz Dedicated Circuit						
Input Power — Plasma System	Refer to Plasma Manufacturer's Manual						

Specifications are subject to change





### Visit HornetCS.com or call 1-844-209-5552 to request a quote



POWERED BY Hupertherm\*

- TF 844-209-5552 430 W Clay
- P 316-755-3683 Valley Center, KS 67147
- г 316-755-1675 Info@HornetCS.com

A Service-Disabled Veteran-Owned Small Business ISOQAR Quality Assured ISO 9001 Certificate #14037A5R001